

Flexible By Design

The Power Feed System simplifies material feeding to the cutting system by automatically adjusting and maintaining consistent tension for any material type. An optional photo-electric edge control unit ensures precise alignment of each ply. Available in one-roll, two-roll, three-roll, six-roll with cart, or flat fold configurations, the Power Feed continuously supplies material for the length of marker or until the roll is consumed.

Single Roll (CRA-355)



Specifications

STANDARDS	ENGLISH	METRIC
Width	78 in.	2.0 m
	84 in.	2.1 m
	96 in.	2.4 m
	108 in.	2.7 m
Custom sizes available in	6 in. width increments	15.2 cm width increments
Maximum Weight	1,500 lbs.	680 kg
Maximum Roll Diameter	30 in.	76 cm

POWER REQUIREMENTS

110V at 15 amps, 1 ph
220V at 8 amps, 1 ph

- Automatic edge control included
- Available in mirror image or standard configuration

Two-Roll, Heavy-Duty (CRA-355)



Specifications

STANDARDS	ENGLISH	METRIC
Maximum Weight	5,000 lbs.	2,268 kg
Weight Capacity per bar	2,500 lbs.	1,134 kg
Maximum Roll Diameter	30 in.	76 cm

POWER REQUIREMENTS

110V at 15 amps, 1 ph
220V at 8 amps, 1 ph

- Automatic edge control included
- Available in mirror image or standard configuration
- Optional upgrade to pneumatic dual disc brake with inflatable bar available

Three-Roll (CRA-355)



Specifications

STANDARDS	ENGLISH	METRIC
Maximum Weight	2,000 lbs.	907 kg
Weight Capacity per bar	750 lbs.	341 kg
Maximum Roll Diameter	20 in.	51 cm

POWER REQUIREMENTS

110V at 15 amps, 1 ph
220V at 8 amps, 1 ph

- Automatic edge control included
- Available in mirror image or standard configuration

With Roll Stand Interface (CRA-355)



Specifications

STANDARDS	ENGLISH	
Maximum Weight	4,000 lbs.	1,814 kg
Weight Capacity per bar	750 lbs.	341 kg
Maximum Roll Diameter	15 in.	38 cm

POWER REQUIREMENTS

110V at 15 amps, 1 ph
220V at 8 amps, 1 ph

- Automatic edge control included
- Available in mirror image or standard configuration
- 6-roll cart
- Includes removable bar supports

Additional 6-Roll Capacity Cart for Material Storage

(not shown)

Specifications

STANDARDS	ENGLISH	METRIC
Maximum Weight	4,000 lbs.	1,814 kg
Maximum Roll Diameter	15 in.	38 cm

- Includes 6 bars (2-3/4" diameter)
- Includes 6 sets of collars (total of 12)
- Available in mirror image or standard configuration
- Specify additional core sizes or cones required
- Larger diameter rolls may be accommodated when 1 or more bar positions are removed
- Includes removable bar supports

Front-End System Only (CRA-355)

(not shown)

Specifications

- 78" (2.0m) and wider, in 6" (15.2cm) increments
- Automatic edge control not available
- Available in mirror image or standard configuration
- No capacity for rolls
- May be used in conjunction with carousel